

ES Series



Part Number	ES10	ES16	ES(S)7	ES(S)10
Pixel pitch	10mm	16mm	7.8mm	10.4mm
LED type	DIP346	DIP346	SMD2727(White)	SMD2727(White)
Pixel configuration	1R1G1B	1R1G1B	1R1G1B	1R1G1B
Size of module	320mmx320mm	320mmx320mm	250mmx250mm	250mmx250mm
Resolution of module	32x32	20x20	32x32	24x24
Density(dots/m ²)	10000	3906	16384	9216
Cabinet material	Alu	Alu	Alu	Alu
Size of cabinet(mm)	1280x960x86.5	1280x960x86.5	1000x1000x83	1000x1000x83
Weight of cabinet	34.5KG	31.7KG	24KG	24KG
Support hanging or not	No	No	No	No
Max power consumption	480/330W/m ²	350W/m ²	630W/m ²	750W/m ²
Average power consumption	160/110W/m ²	120W/m ²	210W/m ²	250W/m ²
Colors	16.7M	16.7M	16.7M	16.7M
Gray scale	16bits	14bits	14bits	14bits
Color temperature	3000-10000K	3000-10000K	3000-10000K	3000-10000K
Driving method	1/4 scanning	Static scanning	1/4 scanning	1/2 scanning
Refresh frequency	1920Hz	1920Hz	1920Hz	1920Hz
Brightness	7500cd/m ²	8000/10000cd/m ²	5500cd/m ²	5500cd/m ²
Brightness control	256 grade	256 grade	256 grade	256 grade
IP grade	IP65	IP65	IP65	IP65